

## L15-GD

Items		Uplink	Downlink
Frequency Range	GSM	890 ~ 915 MHz	935 ~ 960 MHz
	DCS	1710 ~ 1785 MHz	1805 ~ 1880 MHz
Output Power	GSM	0±2 dBm	15±2 dBm
	DCS	0±2 dBm	15±2 dBm
Gain	GSM	25±2 dB	25±2 dB
	DCS	25±2 dB	25±2 dB
ATT(GSM) step of 1 dB	1~10 dB	Δ   ≤1 dB	Δ   ≤1 dB
	10~20 dB	Δ   ≤1 dB	Δ   ≤1 dB
	20~25 dB	Δ   ≤1.5 dB	Δ   ≤1.5 dB
ATT(DCS) step of 1 dB	1~10 dB	Δ   ≤1 dB	Δ   ≤1 dB
	10~20 dB	Δ   ≤1 dB	Δ   ≤1 dB
	20~25 dB	Δ   ≤1.5 dB	Δ   ≤1.5 dB
ALC Active 10 dB	GSM	Δ   ≤2 dB	Δ   ≤2 dB
	DCS	Δ   ≤2 dB	Δ   ≤2 dB
Ripple in Band	GSM	≤6 dB	≤6 dB
	DCS	≤8 dB	≤8 dB
Intermodulation Products	GSM	≤-36dBm	≤-36dBm
	DCS	≤-30 dBm	≤-30 dBm
Spurious Emission	9KHz~1GHz	≤-36 dBm	≤-36 dBm
	1GHz~12.75GHz	≤-30 dBm	≤-30 dBm
Noise Figure @ max. gain	GSM	≤8 dB	—
	DCS	≤8 dB	—
VSWR	GSM	≤2	≤2
	DCS	≤2	≤2
Time delay	GSM	≤1.5 μs	≤1.5 μs
	DCS	≤1.5 μs	≤1.5 μs
LED Indication	Power ON	Green	
	Power OFF	No Light	
Alarm (GSM)	ALC not Active	—	Green
	ALC Active 5~10dB	—	Orange
	ALC Active 15~20dB	—	Red
Alarm (DCS)	ALC not Active	—	Green
	ALC Active 5~10dB	—	Orange
	ALC Active 15~20dB	—	Red
Power Supply		DC:12 V	
Power Consumption		< 20 W	
RF Connector		N-Female	
Environment Conditions		IP40	
Humidity		< 90%	

## L15-GD

Items	Uplink	Downlink
Operating Temperature	-10°C ~ +55°C	